



SOLDERABLE ENAMEL WIRE DATA SHEET

The wire requires a soldering iron temperature of 400°C+ to remove the enamel. (Weller bit temperature code 8 or 9 or Temperature Controlled Iron)

- ***Solderable Enamelled Copper Wire
- *Colours – gold/copper, pink/red, green, violet/blue and assorted bobbins coated in self-fluxing polyurethane, conforming to BS4520
- **Grade 2 (now incorporated within BS6811 Section 1, Pt3)
- Suitable for prototype wiring, PCB track repairs, shorting links and coil forming

Maximum continuous temperature: +120°C

Suitable soldering temperature: 400-480°C

Insulation Thickness

38 swg 0.012 mm Grade 2

36 swg 0.014 mm Grade 2

Resistance: 0.967 Ohms/m typ.

Current Rating

38 swg 82 MA

36 swg 131 MA

Spool Length (Average)

38 swg 38 m

36 swg 27 m

Insulation Breakdown: 1500 V RMS

Bobbins sold 4 per pack

Product: Colour

RRP-C-105: Copper/Gold

RRP-G-105: Green

RRP-P-105: Pink/Red

RRP-V-105: Violet/Blue

RRP-A-105: Assorted – one of each of the above

Wire Diameter: 1/0.15mm (38 SWG)

Product: Colour

RRW-C-105: Copper/Gold

RRW-G-105: Green

RRW-P-105: Pink/Red

RRW-V-105: Violet/Blue

RRW-A-105: Assorted – one of each of the above

Wire Diameter: 1/0.19mm (36SWG)

*The colours can vary, therefore there may be a difference between one batch and another as supplied by our manufacturer.

** Due to occasional supply difficulties, the wire diameters may vary: 0.19mm may be offered as 0.20mm & 0.15mm may be offered as 0.16mm. Also, the grade may vary from Grade 2 to Grade 1. ***Caution: Emits toxic vapour when soldered. Ventilate area well.